

Appendix F FORM 2-F - STORM WATER ASSOCIATED WITH  
INDUSTRIAL ACTIVITY (ISW) Form 2F. [New addition to  
regulation]

---



**NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM (NPDES) PERMIT APPLICATION**

**FORM 2-F - STORM WATER ASSOCIATED WITH INDUSTRIAL ACTIVITY (ISW)**

**I. Outfall Location**

For each outfall, list the latitude and longitude of its location to the nearest 15 seconds and the name of the receiving water.

A. Outfall Number (list)	B. Latitude		C. Longitude		D. Receiving Stream (name)

**II. Improvements**

A. Are you now required by any Federal, State, or local authority to meet any implementation schedule for the construction, upgrading or operation of wastewater treatment equipment or practices or any other environmental programs which may affect the discharges described in this application? This includes, but is not limited to, permit conditions, administrative or enforcement orders, enforcement compliance schedule letters, stipulations, court orders, and grant or loan conditions. areas, areas where pesticides, herbicides, soil conditioners and fertilizers are applied; each of its hazardous waste treatment, storage or disposal units (including each area not required to have a RCRA permit which is used for accumulating hazardous waste under 40 CFR 262.34); each well where fluids are injected underground; springs, and other surface water bodies which receive storm water discharges from the facility.

1. Identification of Conditions Agreements, Etc.	2. Affected Outfalls		3. Brief Description of Project	4. Final Compliance Date	
	Number	Source of Discharge		required	projected

B. You may attach additional sheets describing any additional water pollution (or other environmental projects which may affect your discharges) you now have under way or which you plan. Indicate whether each program is now under way or planned, and indicate your actual or planned schedules for construction.

**III. Site Drainage Map**

Attach a site drainage map showing topography (or indicating the outline of drainage areas served by the outfall(s) covered in the application if a topographic map is unavailable) depicting the facility including: each of its intake and discharge structures; the drainage area of each storm water outfall; paved areas and buildings within the drainage area of each storm water outfall, each known past or present areas used for outdoor storage or disposal of significant materials, each existing structural control measure to reduce pollutants in storm water runoff, materials loading and access areas, areas where pesticides, herbicides, soil conditioners and fertilizers are applied; each of its hazardous waste treatment, storage or disposal units (including each area not required to have a RCRA permit which is used for accumulating hazardous waste under 40 CFR 262.34); each well where fluids are injected underground; springs, and other surface water bodies which receive storm water discharges from the facility.

**IV. Narrative Description of Pollutant Sources**

A. For each outfall, provide an estimate of the area (include units) of impervious surfaces (including paved areas and building roofs) drained to the outfall, and an estimate of the total surface area drained by the outfall.

Outfall Number	Area of Impervious Surface <i>(provide units)</i>	Total Area Drained <i>(provide units)</i>	Outfall Number	Area of Impervious Surface <i>(provide units)</i>	Total Area Drained <i>(provide units)</i>

B. Provide a narrative description of significant materials that are currently or in the past three years have been treated, stored, or disposed in a manner to allow exposure to storm water; method of treatment, storage, or disposal; past and present materials management practices employed, in the last three years, to minimize contact by these materials with storm water runoff; materials loading and access areas; and the location, manner, and frequency in which pesticides, herbicides, soil conditioners, and fertilizers are applied.

C. For each outfall, provide the location and a description of existing structural and nonstructural control measures to reduce pollutants in storm water runoff; and a description of the treatment the storm water receives, including the schedule and type of maintenance for control and treatment measures and the ultimate disposal of any solid or fluid wastes other than by discharge.

Outfall Number	Treatment	List Codes from Table 2F-1

**V. Nonstormwater Discharges**

A. I certify under penalty of law that the outfall(s) covered by this application have been tested or evaluated for the presence of nonstormwater discharges, and that all stormwater discharges from these outfall(s) are identified in either an accompanying Form 2 or Form 3 application for the outfall.

Name and Official Title <i>(type or print)</i>	Signature	Date Signed

B. Provide a description of the method used, the date of any testing, and the onsite drainage points that were directly observed during a test.

**VI. Significant Leaks or Spills**

Provide existing information regarding the history of significant leaks or spills of toxic or hazardous pollutants at the facility in the last three years, including the approximate date and location of the spill or leak, and the type and amount of material released.

**VII. Discharge Information**

A,B,C, & D: See instructions before proceeding. Complete one set of tables for each outfall. Annotate the outfall number in the space provided. Tables VII-A, VII-B, and VII-C are included on pages 2F- page 4 and 2F - page 5.

E: Potential discharges not covered by analysis - Is any pollutant listed in Table 2F-2 a substance or a component of a substance which you currently use or manufacture as an intermediate or final product or byproduct?

Yes (list all such pollutants below)

No

**VIII. Biological Toxicity Testing Data**

Do you have any knowledge or reason to believe that any biological test for acute or chronic toxicity has been made on any of your discharges or on a receiving water in relation to your discharge within the last 3 years?

Yes (list all such pollutants below)

No

**IX. Certification**

*I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing*

Name (type or print)

Title

Signature

Date





## Discharge of Storm Water Associated with Industrial Activity

### Item I

You may use the map you provided with Form 1 to determine the latitude and longitude of each of your outfalls and the name of the receiving water.

### Item II-A

If you check "yes" to this question, complete all parts of the chart, or provide a reference to any previous submission you have made containing the same information.

### Item II-B

You are not required to submit a description of future pollution control projects if you do not wish to or if none is planned.

### Item III

Attach a site map showing topography (or indicating the outline of drainage areas served by the outfall(s) covered in the application) depicting the facility including:

- a) each of its drainage and discharge structures;
- b) the drainage area of each storm water outfall;
- c) paved areas and buildings within the drainage area of each storm water outfall, each known past or present area used for outdoor storage or disposal of significant materials, each existing structural control measure to reduce pollutants in storm water runoff, materials loading and access areas, areas where pesticides, herbicides, soil conditioners and fertilizers are applied;
- d) each of its hazardous waste treatment, storage or disposal facilities (including each area not required to have a RCRA permit which is used for accumulating hazardous waste for less than 90 days under 40 CFR 262.34) ;
- e) each well where fluids from the facility are injected underground; and
- f) springs, and other surface water bodies which receive storm water discharges from the facility;

### Item IV-A

For each outfall, provide an estimate of the area drained by the outfall which is covered by impervious surfaces. For the purpose of this application, impervious surfaces are surfaces where storm water runs off at rates that are significantly higher than background rates (e.g., predevelopment levels) and include paved areas, building roofs, parking lots, and roadways. Include an estimate of the total area (including all impervious and pervious areas) drained by each outfall. The site map required under Item III can be used to estimate the total area drained by each outfall.

### Item IV-B

Provide a narrative description of significant materials that are currently or in the past three years have been treated, stored, or disposed in a manner to allow exposure to storm water; method of treatment,

storage or disposal of these materials; past and present materials management practices employed, in the last three years, to minimize contact by these materials with storm water runoff; materials loading and access areas; and the location, manner, and frequency in which pesticides, herbicides, soil conditioners, and fertilizers are applied. Significant materials should be identified by chemical name, form (e.g., powder, liquid, etc.), and type of container or treatment unit. Indicate any materials treated, stored, or disposed of together. "Significant materials" includes, but is not limited to: raw materials; fuels; materials such as solvents, detergents, and plastic pellets; finished materials such as metallic products; raw materials used in food processing or production; hazardous substances designated under Section 101(14) of CERCLA; any chemical the facility is required to report pursuant to Section 313 of Title III of SARA; fertilizers; pesticides; and waste products such as ashes, slag and sludge that have the potential to be released with storm water discharges.

#### **Item IV-C**

For each outfall, structural controls include structures which enclose material handling or storage areas, covering materials, berms, dikes, or diversion ditches around manufacturing, production, storage or treatment units, retention ponds, etc. Nonstructural controls include practices such as spill prevention plans, employee training, visual inspections, preventive maintenance, and housekeeping measures that are used to prevent or minimize the potential for releases of pollutants.

#### **Item V**

Provide a certification that all outfalls that should contain storm water discharges associated with industrial activity have been tested or evaluated for the presence of non-storm water discharges which are not covered by an NPDES permit. Tests for such non-storm water discharges may include smoke tests, fluorometric dye tests, analysis of accurate schematics, as well as other appropriate tests. Part B must include a description of the method used, the date of any testing, and the onsite drainage points that were directly observed during a test. All non-storm water discharges must be identified in a Form 2, Form 3 or Form 4 which must accompany this application (see general instructions for a description of when Form 2, Form 3 or Form 4 must be submitted).

#### **Item VI**

Provide a description of existing information regarding the history of significant leaks or spills of toxic or hazardous pollutants at the facility in the last three years.

#### **Item VII-A, B, and C**

These items require you to collect and report data on the pollutants discharged from each of your outfalls. Each part of this item addresses a different set of pollutants and must be completed in accordance with the specific instructions for that part. The following general instructions apply to the entire item.

#### **General Instructions**

Part A requires you to report at least one analysis for each pollutant listed. Parts B and C require you to report analytical data in two ways. For some pollutants addressed in Parts B and C, if you know or have reason to know that the pollutant is present in your discharge, you may be required to list the pollutant and test (sample and analyze) and report the levels of the pollutants in your discharge. For all other pollutants addressed in Parts B and C, you must list the pollutant if you know or have reason to know that the pollutant is present in the discharge, and either report quantitative data for the pollutant or briefly describe the reasons the pollutant is expected to be discharged. (See specific instructions on the form and below for Parts A through C.) Base your determination that a pollutant is present in or absent from your discharge on your knowledge of your raw materials, material management practices, maintenance chemicals, history of spills and releases, intermediate and final products and byproducts, and any previous analyses known to you of your effluent or similar effluent.

A. Sampling: The collection of the samples for the reported analyses should be supervised by a person experienced in performing sampling of industrial wastewater or storm water discharges. You may contact the department for detailed guidance on sampling techniques and for answers to specific questions. Any specific requirements contained in the applicable analytical methods must be followed for sample containers, sample preservation, holding times, the collection of duplicate samples, etc. The time when you sample should be representative, to the extent feasible, of your treatment system operating properly with no system upsets. Samples should be collected from the center of the flow channel, where turbulence is at a maximum, at a site specified in your present permit, or at any site adequate for the collection of a representative sample.

For pH, temperature, cyanide, total phenols, residual chlorine, oil and grease, and fecal coliform, grab samples taken during the first 30 minutes (or as soon thereafter as practicable) of the discharge must be used (you are not required to analyze a flow-weighted composite for these parameters). For all other pollutants both a grab sample collected during the first 30 minutes (or as soon thereafter as practicable) of the discharge and a flow-weighted composite sample must be analyzed. However, a minimum of one grab sample may be taken for effluents from holding ponds or other impoundments with a retention period of greater than 24 hours.

All samples shall be collected from a discharge resulting from a storm event that is greater than 0.1 inches and at least 72 hours from the previously measurable (greater than 0.1 inch rainfall) storm event. Where feasible, the variance in the duration of the event and the total rainfall of the event should not exceed 50 percent from the average or median rainfall event in that area.

Data from samples taken in the past may be used, provided that:

- i. All data requirements are met;
- ii. Sampling was done no more than three years before submission; and
- iii. All data are representative of the present discharge.

Among the factors which would cause the data to be unrepresentative are significant changes in production level, changes in raw materials, processes, or final products, and changes in storm water treatment. The Director may request additional information, including current quantitative data, if they determine it to be necessary to assess your discharges. The Director may allow or establish appropriate site-specific sampling procedures or requirements, including sampling locations, the season in which the sampling takes place, the minimum duration between the previous measurable storm event and the storm event sampled, the minimum or maximum level of precipitation required for an appropriate storm event, the form of precipitation sampled (snow melt or rainfall), protocols for collecting samples under 40 CFR Part 136, and additional time for submitting data on a case-by-case basis.

**B. Reporting:** All levels must be reported as concentration and as total mass. You may report some or all of the required data by attaching separate sheets of paper instead of filling out pages 2F-4 and 2F-5 if the separate sheets contain all the required information in a format which is consistent with pages 2F-4 and 2F-5 in spacing and in identification of pollutants and columns. Use the following abbreviations in the columns headed "Units."

<b>Concentration</b>		<b>Mass</b>	
ppm	parts per million	lbs	pounds
mg/l	milligrams per liter	ton	tons (English tons)
ppb	parts per billion	mg	milligrams
ug/l	micrograms per liter	g	grams
kg	kilograms	T	tonnes (metric tons)

All reporting of values for metals must be in terms of "total metal," unless:

1. An applicable, promulgated effluent limitation or standard specifies the limitation for the metal in dissolved, valent, or total form; or
2. All approved analytical methods for the metal inherently measure only its dissolved form (e.g., hexavalent chromium) ; or

The department has determined that in establishing case-by-case limitations it is necessary to express the limitations on the metal in dissolved, valent, or total form to carry out the provisions of the CWA. If you measure only one grab sample and one flow-weighted composite sample for a given outfall, complete only the "Maximum Values" columns and insert "1" into the "Number of Storm Events Sampled" column. The permitting authority may require you to conduct additional analyses to further characterize your discharges.

If you measure more than one value for a grab sample or a flow-weighted composite sample for a given outfall and those values are representative of your discharge, you must report them. You must describe your method of testing and data analysis. You also must determine the average of all values within the last year and report the concentration and mass under the "Average Values" columns, and the total number of storm events sampled under the "Number of Storm Events Sampled" columns.

**C. Analysis:** You must use test methods promulgated in 40 CFR Part 136; however, if none has been promulgated for a particular pollutant, you may use any suitable method for measuring the level of the pollutant in your discharge. If you have two or more substantially identical outfalls, you may request permission to sample and analyze only one outfall and submit the results of the analysis for other substantially identical outfalls. If your request is granted by the department, on a separate sheet attached to the application form, identify which outfall you did test, and describe why the outfalls which you did not test are substantially identical to the outfall which you did test.

#### **Part VII-A**

Part VII-A must be completed by all applicants for all outfalls who must complete Form 2F.

Analyze a grab sample collected during the first thirty minutes (or as soon thereafter as practicable) of the discharge and flow-weighted composite samples for all pollutants in this Part, and report the results except use only grab samples for pH and oil and grease. The "Average Values" column is not compulsory but should be filled out if data are available.

#### **Part VII-B**

List all pollutants that are limited in an effluent guideline which the facility is subject to (see 40 CFR Subchapter N to determine which pollutants are limited in effluent guidelines) or any pollutant listed in the facility's NPDES permit for its process wastewater (if the facility is operating under an existing NPDES permit). Complete one table for each outfall. The "Average Values" column is not compulsory but should be filled out if data are available.

Analyze a grab sample collected during the first thirty minutes of the discharge and flow-weighted composite samples for all pollutants in this Part, and report the results, except as provided in the General Instructions.

#### **Part VII-C**

Part VII-C must be completed by all applicants for all outfalls which discharge storm water associated with industrial activity, or that the State of Iowa is evaluating for designation as a significant contributor of

pollutants to waters of the state, or as contributing to a violation of a water quality standard. Use both a grab sample and a composite sample for all pollutants you analyze for in this part except use grab samples for residual chlorine and fecal coliform. The "Average Values" column is not compulsory but should be filled out if data are available. Part C requires you to address the pollutants in Table 2F-2, 2F-3, and 2F-4 for each outfall. Pollutants in each of these Tables are addressed differently.

**Table 2F-2:** For each outfall, list all pollutants in Table 2F-2 that you know or have reason to believe are discharged (except pollutants previously listed in Part VII-B). If a pollutant is limited in an effluent guideline limitation to which the facility is subject (e.g., use of TSS as an indicator to control the discharge of iron and aluminum), the pollutant should be listed in Part VII-B. If a pollutant in table 2F-2 is indirectly limited by an effluent guideline limitation through an indicator, you must analyze for it and report data in Part VII-C. For other pollutants listed in Table 2F-2 (those not limited directly or indirectly by an effluent limitation guideline), that you know or have reason to believe are discharge, you must either report quantitative data or briefly describe the reason the pollutant is expected to be discharged.

**Table 2F-3:** For each outfall, list all pollutants in Table 2F-3 that you know or have reason to believe are discharged. For every pollutant in Table 2F-3 expected to be discharged in concentrations of 10 ppb or greater, you must submit quantitative data. For acrolein, acrylonitrile, 2,4 dinitrophenol, and 2-methyl-4,6 dinitrophenol, you must submit quantitative data if any of these four pollutants is expected to be discharged in concentrations of 100 ppb or greater. For every pollutant expected to be discharged in concentrations less than 10 ppb (or 100 ppb for the four pollutants listed above), then you must either submit quantitative data or briefly describe the reason the pollutant is expected to be discharged.

**Small Business Exemption** - If you are a "small business," you are exempt from the reporting requirements for the organic toxic pollutants listed in Table 2F-3. There are two ways in which you can qualify as a "small business".

i.If your facility is a coal mine, and if your probable total annual production is less than 100,000 tons per year, you may submit past production data or estimated future production (such as a schedule of estimated total production under 30 CFR 795.14(c)) instead of conducting analyses for the organic toxic pollutants.

ii.If your facility is not a coal mine, and if your gross total annual sales for the most recent three years average less than \$100,000 per year (in second quarter 1980 dollars), you may submit sales data for those years instead of conducting analyses for the organic toxic pollutants. The production or sales data must be for the facility which is the source of the discharge.

The production or sales data must be for the facility which is the source of the discharge. The data should not be limited to production or sales for the process or processes which contribute to the discharge, unless those are the only processes at your facility. For sales data, in situations involving intracorporate transfer of goods and services, the transfer price per unit should approximate market prices for those goods and services as closely as possible. Sales figures for years after 1980 should be indexed to the second quarter of 1980 by using the gross national product price deflator (second quarter of 1980=100). This index is available in National Income and Product Accounts of the United States (Department of Commerce, Bureau of Economic Analysis).

**Table 2F-4:** For each outfall, list any pollutant in Table 2F-4 that you know or believe to be present in the discharge and explain why you believe it to be present. No analysis is required, but if you have analytical data, you must report them. Note: Under 40 CFR 117.12(a)(2), certain discharges of hazardous substances listed at 40 CFR 177.21 or 40 CFR 302.4 may be exempted from the requirements of section 311 of CWA, which establishes reporting requirements, civil penalties, and liability for cleanup costs for spills of oil and hazardous substances. A discharge of a particular substance may be exempted if the origin, source, and amount of the discharged substances are identified in the NPDES permit application or in the permit, if the permit contains a requirement for treatment of the discharge, and if the treatment is in place. To apply for an exclusion of the discharge of any hazardous substance from the requirements of section 311, attach additional sheets of paper to your form, setting forth the following information:

1. The substance and the amount of each substance which may be discharged.
2. The origin and source of the discharge of the substance.
3. The treatment which is to be provided for the discharge by:
  - a) An onsite treatment system separate from any treatment system treating your normal discharge;
  - b) A treatment system designed to treat your normal discharge and which is additionally capable of treating the amount of the substance identified under paragraph 1 above; or
  - c) Any combination of the above.

See 40 CFR 117.12(a)(2) and (c), published on August 29, 1979, in 44 FR 50766, or contact the department for further information on exclusions from section 311.

#### **Part VII-D**

If sampling is conducted during more than one storm event, you only need to report the information requested in Part VII-D for the storm event(s) which resulted in any maximum pollutant concentration reported in Part VII-A, VII-B, or VII-C. Provide flow measurements or estimates of the flow rate, and the total amount of discharge for the storm event(s) sampled and the method of flow measurement or estimation. Provide the duration of the storm event(s) sampled, rainfall measurements, or estimates of the storm event which generated the sampled runoff and the duration between the storm event sampled and the end of the previous measurable (greater than 0.1 inch rainfall) storm event.

#### **Part VII-E**

List any toxic pollutant listed in Tables 2F-2, 2F-3, or 2F-4 which you currently use or manufacture as an intermediate or final product or byproduct. In addition, if you know or have reason to believe that 2,3,7,8-tetrachlorodibenzo-p-dioxin (TCDD) is discharged or if you use or manufacture 2,4,5-trichlorophenoxy acetic acid (2,4,5,-T) ; 2-(2,4,5-trichlorophenoxy) propanoic acid (Silvex, 2,4,5,-TP) ; 2-(2,4,5-trichlorophenoxy) ethyl, 2,2-dichloropropionate (Erbon); 0,0 dimethyl 0-(2,4,5-trichlorophenyl) phosphorothioate (Ronnell) ; 2,4,5-trichlorophenol (TCP) ; or hexachlorophene (HCP); then list TCDD. The Director may waive or modify this requirement if you demonstrate that it would be unduly burdensome to identify each toxic pollutant and the Director has adequate information to issue your permit. You may not claim this information as confidential; however, you do not have to distinguish between use or production of the pollutants or list the amounts.

#### **Item VIII**

Self explanatory. The department may ask you to provide additional details after your application is received.

#### **Item X**

See the General Information provided with Form 1 for signature requirements.

**Table 2F-1**

**Codes for Treatment Units**

**Physical Treatment Processes**

1-A	Ammonia Stripping	1-M	Grit Removal
1-B	Dialysis	1-N	Microstraining
1-C	Diatomaceous Earth Filtration	1-O	Mixing
1-D	Distillation	1-P	Moving Bed Filters
1-E	Electrodialysis	1-Q	Multimedia Filtration
1-F	Evaporation	1-R	Rapid Sand Filtration
1-G	Flocculation	1-S	Reverse Osmosis (Hyperfiltration)
1-H	Rotation	1-T	Screening
1-I	Foam Fractionation	1-U	Sedimentation (Settling)
1-J	Freezing	1-V	Slow Sand Filtration
1-K	Gas-Phase Separation	1-W	Solvent Extraction
1-L	Grinding (Comminutors)	1-X	Sorption

**Chemical Treatment Processes**

2-A	Carbon Adsorption	2-G	Disinfection (Ozone)
2-B	Chemical oxidation	2-H	Disinfection (Other)
2-C	Chemical Precipitation	2-I	Electrochemical Treatment
2-D	Coagulation	2-J	Ion Exchange
2-E	Dechlorination	2-K	Neutralization
2-F	Disinfection (Chlorine)	2-L	Reduction

**Biological Treatment Processes**

3-A	Activated Sludge	3-E	Pre-Aeration
3-B	Aerated Lagoons	3-F	Spray Irrigation/Land Application
3-C	Anaerobic Treatment	3-G	Stabilization Ponds
3-D	Nitrification-Denitrification	3-H	Trickling Filtration

**Other Processes**

4-A	Discharge to Surface Water	4-C	Reuse/Recycle of Treated Effluent
4-B	Ocean Discharge Through Outfall	4-D	Underground Injection

**Sludge Treatment and Disposal Processes**

5-A	Aerobic Digestion	5-M	Heat Drying
5-B	Anaerobic Digestion	5-N	Heat Treatment
5-C	Belt Filtration	5-O	Incineration
5-D	Centrifugation	5-P	Land Application
5-E	Chemical Conditioning	5-Q	Landfill
5-F	Chlorine Treatment	5-R	Pressure Filtration
5-G	Composting	5-S	Pyrolysis
5-H	Drying Beds	5-T	Sludge Lagoons
5-I	Elutriation	5-U	Vacuum Filtration
5-J	Floatation Thickening	5-V	Vibration
5-K	Freezing	5-W	Wet Oxidation
5-L	Gravity Thickening		

## Table 2F-2

### Conventional and Nonconventional Pollutants Required To Be Tested by Existing Discharger if Expected To Be Present

Bromide  
Chlorine, Total Residual  
Color  
Fecal Coliform  
Fluoride  
Nitrate-Nitrite  
Nitrogen, Total Kjeldahl  
Oil and Grease  
Phosphorus, Total Radioactivity  
Sulfate  
Sulfide  
Sulfite  
Surfactants  
Aluminum, Total  
Barium, Total  
Boron, Total  
Cobalt, Total  
Iron, Total  
Magnesium, Total  
Molybdenum, Total  
Tin, Total  
Titanium, Total

**Table 2F-3****Toxic pollutants required to be identified by applicant if expected to be present****Toxic Pollutants and Total Phenol**

Antimony	Copper, Total	Silver, Total
Arsenic, Total	Lead, Total	Thallium, Total
Beryllium, Total	Mercury, Total	Zinc, Total
Cadmium, Total	Nickel, Total	Cyanide, Total
Chromium, Total	Selenium, Total	Phenols, Total

**GC/MS Fraction Volatiles Compounds**

Acrolein	Dichlorobromomethane	1,1,2,2,-Tetrachloroethane
Acrylonitrile	1,1-Dichloroethane	Tetrachloroethylene
Benzene	1,2-Dichloroethane	Toluene
Bromoform	1,1-Dichloroethylene	1,2-Trans-Dichloroethylene
Carbon Tetrachloride	1,2-Dichloropropane	1,1,1-Trichloroethane
Chlorobenzene	1,3-Dichloropropylene	1,1,2-Trichloroethane
Chlorodibromomethane	Ethylbenzene	Trichloroethylene
Chloroethane	Methyl Bromide	Vinyl Chloride
2-Chloroethylvinyl Ether	Methyl Chloride	
Chloroform	Methylene Chloride	

**Acid Compounds**

2-Chlorophenol	2,4-Dinitrophenol	Pentachlorophenol
2,4-Dichlorophenol	2-Nitrophenol	Phenol
2,4-Dimethylphenol	4-Nitrophenol	2,4,6-Trichlorophenol
4,6-Dinitro-O-Cresol	p-Chloro-M-Cresol	

**Base/Neutral**

Acenaphthene	2-Chloronaphthalene	Fluoranthene
Acenaphthylene	4-Chlorophenyl Phenyl Ether	Fluorene
Anthracene	Chrysene	Hexachlorobenzene
Benzidine	Dibenzo(a,h)anthracene	Hexachlorobutadiene
Benzo(a)anthracene	1,2-Dichlorobenzene	Hexachloroethane
Benzo(a)pyrene	1,3-Dichlorobenzene	Indeno(1,2,3-cd)pyrene
3,4-Benzofluoranthene	1,4-Dichlorobenzene	Isophorone
Benzo(ghi)perylene	3,3'-Dichlorobenzidine	Napthalene
Benzo(k)fluoranthene	Diethyl Phthalate	Nitrobenzene
Bis(2-chloroethoxy)methane	Dimethyl Phthalate	N-Nitrosodimethylamine
Bis(2-chloroethyl)ether	Di-N-Butyl Phthalate	N-Nitrosodi-N-Propylamine
Bis(2-chloroisopropyl)ether	2,4-Dinitrotoluene	N-Nitrosodiphenylamine
Bis(2-ethylhexyl) phthalate	2,6-Dinitrotoluene	Phenanthrene
4-Bromophenyl Phenyl Ether	Di-N-Octylphthalate	Pyrene
Butylbenzyl Phthalate	1,2-Diphenylhydrazine (as Azobenzene)	1,2,4-Trichlorobenzene

## Pesticides

Aldrin	Dieldrin	PCB-1254
Alpha-BHC	Alpha-Endosulfan	PCB-1221
Beta-BHC	Beta-Endosulfan	PCB-1232
Gamma-BHC	Endosulfan Sulfate	PCB-1248
Delta-BHC	Endrin	PCB-1260
Chlordane	Endrin Aldehyde	PCB-1016
4,4'-DDT	Heptachlor	Toxaphene
4,4'-DDE	Heptachlor Epoxide	
4,4'-DDD	PCB-1242	

## Table 2F-4

**Hazardous substances required to be identified by applicant if expected to be present**

### Toxic Pollutant

Asbestos

### Hazardous Substances

Acetaldehyde	Dinitrobenzene	Napthenic acid
Allyl alcohol	Diquat	Nitrotoluene
Allyl chloride	Disulfoton	Parathion
Amyl acetate	Diuron	Phenolsulfonate
Aniline	Epichlorohydrin	Phosgene
Benzonitrile	Ethion	Propargite
Benzyl chloride	Ethylene diamine	Propylene oxide
Butyl acetate	Ethylene dibromide	Pyrethrins
Butylamine	Formaldehyde	Quinoline
Carbaryl	Furfural	Resorcinol
Carbofuran	Guthion	Stronthium
Carbon disulfide	Isoprene	Strychnine
Chlorpyrifos	Isopropanolamine	Styrene
Coumaphos	Kelthane	2,4,5-T (2,4,5-
		Trichlorophenoxyacetic acid)
Cresol	Kepone	TDE (Tetrachlorodiphenyl
Crotonaldehyde	Malathion	ethane)
		2,4,5-TP [2-(2,4,5-
Cyclohexane	Mercaptodimethur	Trichlorophenoxy)
2,4-D (2,4-	Methoxychlor	propanoic acid]
Dichlorophenoxyacetic		
acid)	Methyl mercaptan	
Diazinon	Methyl methacrylate	
Dicamba	Methyl parathion	
Dichlobenil	Mevinphos	
Dichlone	Mexacarbate	
2,2-Dichloropropionic acid	Monoethyl amine	
Dichlorvos	Monomethyl amine	
Diethyl amine	Naled	
Dimethyl amine		
Trichlorofan		
Triethylamine		
Trimethylamine		
Uranium		
Vanadium		
Vinyl acetate		
Xylene		
Xylenol		
Zirconium		